

styledcmd

Paolo De Donato

13 December 2022

styledcmd is a \LaTeX package that allows you to create and manage different versions of your macro in order to be able to choose the better style for every occasion and avoid rewriting code each time.

1 How can you include it in your project?

You need only to have the file `styledcmd.sty` in your current working directory. Otherwise you can manually install it inside your preferred \LaTeX compiler (for example TeXLive or MiKTeX) in order to make it available for all your projects. Instructions for manually install a package can be found on Internet.

Then once you've added it you can include in your project with this command:

```
\usepackage{styledcmd}
```

2 How do you use it?

You can create a formatted macro via the following command

```
\newstyledcmd \newstyledcmd {\macro name} {\style name} [(number of arguments)] {\code}
```

```
\renewstyledcmd  
\providestyledcmd
```

it has the same syntax of `\newcommand` except for the $\langle style name \rangle$ argument that specify the style. This macro alone creates commands $\langle macro name \rangle$ and $\langle macro name \rangle[\langle style name \rangle]$ that both expand as $\langle code \rangle$.

The most important feature is that you can call `\newstyledcmd` multiple times with the same $\langle macro name \rangle$ but different $\langle style name \rangle$, in this way each of $\langle macro name \rangle[\langle style name \rangle]$ expands to $\langle code \rangle$ associated to specified $\langle style name \rangle$. Notice that if you don't specify a style with just calling `\metamacro name` then it expands as the first created style, that style is the *default* one for such command.

As an example these commands

```
\newstyledcmd{\saluto}{informal}[1]{Hi #1}  
\newstyledcmd{\saluto}{formal}[1]{Good morning #1}
```

define the two formats `informal` and `formal` for macro `\saluto`. Once you've created these two styles for `\saluto` you can use it with or without the style name argument, for example these commands

```
\saluto{uncle}  
\saluto[informal]{uncle}  
\saluto[formal]{uncle}
```

will be expanded respectively as Hi uncle, Hi uncle, Good morning uncle. With the same syntax you can use `\renewstyledcmd` and `\providestyledcmd` with the same meaning of `\renewcommand` and `\providecommand` respectively.

3 How do you change the default style?

In order to change the default style (the one used when you don't choose explicitly a style) you need to execute the following command

```
\SetGlobalStyle \SetGlobalStyle {\langle command name \rangle} {\langle new default style name \rangle}
```

For example in order to change the default style of command `\saluto` from `informal` to `formal` you need to execute command `\SetGlobalStyle{\saluto}{formal}`. With this command the output of preceding commands will instead be Good morning uncle, Hi uncle, Good morning uncle.

4 Customize parameters with xparse

styledcmd loads automatically the xparse package for internal reasons. You can also define new styled commands with the same syntax used by `\NewDocumentCommand` with the following command

```
\NewDocStyledCMD \NewDocStyledCMD {\langle command name \rangle} {\langle format name \rangle} {\langle arguments format \rangle} {\langle code \rangle}
\RenewDocStyledCMD
\ProvideDocStyledCMD
```

For example we can create the following two styles

```
\NewDocStyledCMD{\prova}{stylea}{r<>}{Stile 1 #1}
\NewDocStyledCMD{\prova}{styleb}{r<>}{Stile 2 #1}
```

in order to execute

```
\prova<Hello>
\prova[stylea]<Hello>
\prova[styleb]<Hello>
```

which are expanded respectively as Stile 1 Hello; Stile 1 Hello; Stile 2 Hello. Notice that the first optional argument passed to a command defined via `\NewDocStyledCMD` will always be interpreted as a style argument, so you should use another syntax for optional arguments or use a mandatory argument for the first place.

For example this declaration `\NewDocStyledCMD{\bad}{style}{o m}{Bad declaration}` should be avoided since for example `\bad[arg1]{arg2}` will interpret `arg1` as a style name and not as the first optional argument for `\bad`.

5 Expandable commands

Commands created by `\newstylecmd` doesn't work very well in expansion only context due to the presence of optional style argument. In order to be able to create expandable commands you should instead use

<code>\newstylecmdExp</code>	<code>\newstylecmdExp {\langle macro name \rangle} {\langle style name \rangle} [\langle number of arguments \rangle] {\langle code \rangle}</code>
<code>\renewstylecmdExp</code>	
<code>\providestylecmdExp</code>	

Despite commands created with `\newstylecmd` the style name of commands created by `\newstylecmdExp` are always mandatory and must be passed inside curly braces. In order to use the default style just pass an empty string as style name.

For example this code

```
\newstylecmdExp{\expCMD}{sty1}{Style 1}
\newstylecmdExp{\expCMD}{sty2}{Style 2}

\expCMD{}
\expCMD{sty1}
\expCMD{sty2}
```

expand as Style 1 Style 1 Style 2

6 Groups

The group mechanism is very different from `stylecmd 1.2` and preceding versions. From 2.0 styled commands can be added to a group in order to change together their style. Groups are automatically created when you're trying to add commands to it:

<code>\AddCMDToGroup</code>	<code>\AddCMDToGroup {\langle group name \rangle} {\langle comma list of commands \rangle}</code>
-----------------------------	---

You can change the default style for each member of a group with

<code>\SetGroupStyle</code>	<code>\SetGroupStyle {\langle group name \rangle} {\langle style name \rangle}</code>
-----------------------------	---

Suppose you've created the following styled commands:

```
\newstylecmd{\LenUnit}{SI}{metre}
\newstylecmd{\MasUnit}{SI}{kilo}

\newstylecmd{\LenUnit}{old}{yard}
\newstylecmd{\MasUnit}{old}{pound}
```

Commands `\LenUnit`, `\MasUnit` will expand as metre, kilo respectively since `SI` is the default style. We've used `\newstylecmd` but you could use also `\NewDocStyledCMD`, `\newstylecmdExp` or any other command generated as in section 7. To add these two commands to group `Units` run

```
\AddCMDToGroup{Units}{\LenUnit, \MasUnit}
```

If you want to set `old` as the default style for these commands just run

`\SetGroupStyle{Units}{old}`

now `\LenUnit`, `\MasUnit` will expand as yard, pound respectively.

Notice that if the specified group already exists then `\AddCMDToGroup` just appends the specified commands to it. In particular this

```
\AddCMDToGroup{Units}{\LenUnit}
\AddCMDToGroup{Units}{\MasUnit}
```

is equivalent to write

```
\AddCMDToGroup{Units}{\LenUnit, \MasUnit}
```

7 Advanced usage

This section is for advanced users and package maintainers that knows L^AT_EX3, It's not needed to use `styledcmd` daily or creating documents. If `\newstyledcmd`, `\NewDocStyledCMD` and `\newstyledcmdExp` aren't suitable for you it's possible to create a custom styled command generator, but we first need to know a bit of the internal structure of `styledcmd`.

What you see as a styled command it's instead a collection of different macros:

- multiple *effective styled commands* (*ES commands*), one for each style;
- a single *dispatch command* that's called by the user and expands to the specified ES command.

<code>\stycmd_generate:NNN</code>	<code>\stycmd_generate:NNN</code> $\langle generator\ name \rangle$ $\langle ES\ commands\ generator \rangle$ $\langle dispatch\ command\ generator \rangle$
<code>\stycmd_generate:NN</code>	<code>\stycmd_generate:NN</code> $\langle generator\ name \rangle$ $\langle ES\ commands\ generator \rangle$

Creates a generator of styled commands with name $\langle generator\ name \rangle$. Argument $\langle ES\ commands\ generator \rangle$ is used to create ES commands and should accept a macro name as the first argument, but there aren't other restrictions on remaining arguments. Suitable ES commands generators are `\newcommand` and `\NewDocumentCommand`.

Argument $\langle dispatch\ command\ generator \rangle$ should generate the dispatch command. Despite $\langle ES\ commands\ generator \rangle$ this command must have only one parameter, a string representing the command to be created. Suitable values for this parameter are:

<code>\stycmd_xparsecmd:N</code>	<code>\stycmd_xparsecmd:N</code> $\langle command \rangle$
----------------------------------	--

Creates the dispatch command with `\ProvideDocumentCommand` with optional style name parameter (used in `\newstyledcmd` and `\NewDocStyledCMD`).

<code>\stycmd_expcmd:N</code>	<code>\stycmd_expcmd:N</code> $\langle command \rangle$
-------------------------------	---

Creates the dispatch command with `\providecommand` with mandatory style name parameter (used in `\newstyledcmdExp`).

If you don't specify the dispatch command generator (by using the NN variant) `\stycmd_xparsecmd:N` is used implicitly.

`\stycmd_generate_renew:NN` `\stycmd_generate_renew:NN` *<updater name>* *<ES commands generator>*

Creates command `\<updater name>` that modifies styles of commands already generated, like `\renewcommand` edits commands generated by `\newcommand`.

For example if you have `\createA` that creates commands and `\editA` that edits commands generated by `\createA` then

```
\stycmd_generate:NN \createStyledA \createA
```

creates styled commands by using `\createA` and

```
\stycmd_generate_renew:NN \editStyledA \editA
```

modifies commands generated by `\createStyledA` (by invoking `\editA`).

8 Implementation

```
1 <*package>
```

```
2 <@@=stycmd>
```

`\c__stycmd_cmdproxy_str` Proxy used to generate styled commands

```
3
4 \str_const:Nx \c__stycmd_cmdproxy_str { \object_address:nn
5   { stycmd }{ proxy } }
6
7 \proxy_create:nnN { stycmd }{ proxy } \c_object_public_str
8 \proxy_push_member:Vnn \c__stycmd_cmdproxy_str { default }{ t1 }
9
```

(End definition for \c__stycmd_cmdproxy_str.)

`__stycmd_cmd:n` Entity name

```
10
11 \cs_new:Nn \__stycmd_cmd:n
12 {
13   \object_address:nn{ stycmd }{ entity - #1 }
14 }
15
```

(End definition for __stycmd_cmd:n.)

`__stycmd_setdef_strip:Nn` Changes the default style

```
16
17 \cs_new_protected:Nn \__stycmd_setdef_aux:nN
18 {
19   \object_member_set:nnn
20   {
21     \__stycmd_cmd:n{ #1 }
22   }
23   { default }
24   { #2 }
25 }
26 \cs_generate_variant:Nn \__stycmd_setdef_aux:nN { nc }
27
```

```

28 \cs_new_protected:Nn \__stycmd_setdef_style:nn
29 {
30   \__stycmd_setdef_aux:nc{ #1 }
31   {
32     \object_macro_adr:nn
33     {
34       \__stycmd_cmd:n{ #1 }
35     }
36     {
37       style - #2
38     }
39   }
40 }
41
42 \cs_generate_variant:Nn \__stycmd_setdef_style:nn { ff }
43
44 \cs_new_protected:Nn \__stycmd_setdef_strip:Nn
45 {
46   \__stycmd_setdef_style:ff{ \cs_to_str:N #1 }
47   { \tl_trim_spaces:n{ #2 } }
48 }
49

```

(End definition for __stycmd_setdef_strip:Nn.)

__stycmd_cmd_define_strip:NNn Define a macro with the specified command

```

50
51 \cs_new_protected:Nn \__stycmd_cmd_define_aux_aux:NN
52 {
53   #1 { #2 }
54 }
55 \cs_generate_variant:Nn \__stycmd_cmd_define_aux_aux:NN { Nc }
56
57 \cs_new_protected:Nn \__stycmd_cmd_define_aux:Nnn
58 {
59   \__stycmd_cmd_define_aux_aux:Nc #1
60   {
61     \object_macro_adr:nn
62     {
63       \__stycmd_cmd:n{ #2 }
64     }
65     {
66       style - #3
67     }
68   }
69 }
70
71 \cs_generate_variant:Nn \__stycmd_cmd_define_aux:Nnn { Nff }
72
73 \cs_new_protected:Nn \__stycmd_cmd_define_strip:NNn
74 {
75   \__stycmd_cmd_define_aux:Nff #1
76   { \cs_to_str:N #2 }{ \tl_trim_spaces:n { #3 } }
77 }
78

```

(End definition for `_stycmd_cmd_define_strip:Nn`.)

`_stycmd_cmd_undef:N` Uses the styled command

```
\_stycmd_cmd_undef:N
  \_stycmd_cmd_undef_aux:Nn
    79
    80 \cs_new:Nn \_stycmd_cmd_undef_aux:n
    81   {
    82     \object_member_use:nn
    83     {
    84       \_stycmd_cmd:n{ #1 }
    85     }
    86     {
    87       default
    88     }
    89   }
    90
    91 \cs_generate_variant:Nn \_stycmd_cmd_undef_aux:n { f }
    92
    93 \cs_new:Nn \_stycmd_cmd_undef:N
    94   {
    95     \_stycmd_cmd_undef_aux:f{ \cs_to_str:N #1 }
    96   }
    97
    98
    99 \cs_new:Nn \_stycmd_cmd_undef_sty:Nn
   100   {
   101     \object_macro_use:nn
   102     {
   103       \_stycmd_cmd:n{ #1 }
   104     }
   105     {
   106       style - #2
   107     }
   108   }
   109
   110 \cs_generate_variant:Nn \_stycmd_cmd_undef_sty:Nn { ff }
   111
   112 \cs_new:Nn \_stycmd_cmd_undef_sty_strip:Nn
   113   {
   114     \_stycmd_cmd_undef_sty:ff{ \cs_to_str:N #1 }
   115     { \tl_trim_spaces:n{ #2 } }
   116   }
   117
```

(End definition for `_stycmd_cmd_undef:N` and `_stycmd_cmd_undef_sty_strip:Nn`.)

`_stycmd_entity_create_strip:Nnn` Creates a new entity if it doesn't exist and execute following code

```
118
119 \cs_new_protected:Nn \_stycmd_entity_create_aux:nnn
120   {
121     \object_if_exist:nF
122     {
123       \_stycmd_cmd:n{ #1 }
124     }
125     {
```

```

126     \object_create:VnnNN \c__stycmd_cmdproxy_str
127     { stycmd }{ entity - #1 }
128     \c_object_global_str
129     \c_object_public_str
130
131     \__stycmd_setdef_style:nn{ #1 }{ #2 }
132
133     #3
134   }
135 }
136
137 \cs_generate_variant:Nn \__stycmd_entity_create_aux:nnn { ffn }
138
139 \cs_new_protected:Nn \__stycmd_entity_create_stripe:Nnn
140 {
141   \__stycmd_entity_create_aux:ffn
142   { \cs_to_str:N #1 }
143   { \tl_trim_spaces:n{ #2 } }
144   { #3 }
145 }
146

```

(End definition for `__stycmd_entity_create_stripe:Nnn`.)

`\stycmd_xparsecmd:N` Defines the main macro with `\ProvideDocumentCommand`.

```

147
148 \cs_new_protected:Nn \stycmd_xparsecmd:N
149 {
150   \ProvideDocumentCommand { #1 } { o }
151   {
152     \IfNoValueTF {##1}
153     {
154       \__stycmd_cmd_undef:N #1
155     }
156     {
157       \__stycmd_cmd_undef:N #1 { ##1 }
158     }
159   }
160 }
161

```

(End definition for `\stycmd_xparsecmd:N`. This function is documented on page 4.)

`\stycmd_expcmd:N` Defines the main macro with `\providecommand` but the style argument is mandatory in order to make the command expandable. To use default style pass an empty argument as style.

```

162
163 \cs_new_protected:Nn \stycmd_expcmd:N
164 {
165   \providecommand { #1 } [1]
166   {
167     \tl_if_empty:nTF {##1}
168     {
169       \__stycmd_cmd_undef:N #1

```

```

170     }
171     {
172     \__stycmd_cmd_usesty_strip:Nn #1 { ##1 }
173     }
174   }
175 }
176

```

(End definition for `\stycmd_expcmd:N`. This function is documented on page 4.)

`\SetGlobalStyle` Change the default style for specified command

```

177
178 \NewDocumentCommand{\SetGlobalStyle}{m m}
179 {
180   \__stycmd_setdef_strip:Nn #1 { #2 }
181 }
182

```

(End definition for `\SetGlobalStyle`. This function is documented on page 2.)

`\stycmd_generate:NNN` Declare the styled version #1 of the macro generator command #2. the `_renew` variant
`\stycmd_generate:NN` requires a preceding declaration
`\stycmd_generate_renew:NN`

```

183
184 \cs_new_protected:Nn \stycmd_generate:NNN
185 {
186   \cs_new_protected:Npn #1 ##1 ##2
187   {
188     \__stycmd_entity_create_strip:Nnn ##1 { ##2 }
189     {
190       #3 ##1
191     }
192     \__stycmd_cmd_define_strip:NNn #2 ##1 { ##2 }
193   }
194 }
195
196 \cs_new_protected:Nn \stycmd_generate:NN
197 {
198   \stycmd_generate:NNN #1 #2 \stycmd_xparsecmd:N
199 }
200
201
202 \cs_new_protected:Nn \stycmd_generate_renew:NN
203 {
204   \cs_new_protected:Npn #1 ##1 ##2
205   {
206     \__stycmd_cmd_define_strip:NNn #2 ##1 { ##2 }
207   }
208 }
209

```

(End definition for `\stycmd_generate:NNN`, `\stycmd_generate:NN`, and `\stycmd_generate_renew:NN`. These functions are documented on page 4.)

`\newstylecmd` Declare a new macro with the specified style name.
`\renewstylecmd` 210 `\stycmd_generate:NN \newstylecmd \newcommand`
`\providestylecmd` 211 `\stycmd_generate_renew:NN \renewstylecmd \renewcommand`
212 `\stycmd_generate:NN \providestylecmd \providecommand`

(End definition for \newstylecmd, \renewstylecmd, and \providestylecmd. These functions are documented on page 1.)

`\NewDocStyledCMD` Declare a new styled macro with the `\NewDocumentCommand` syntax.
`\RenewDocStyledCMD` 213 `\stycmd_generate:NN \NewDocStyledCMD \NewDocumentCommand`
`\ProvideDocStyledCMD` 214 `\stycmd_generate_renew:NN \RenewDocStyledCMD \RenewDocumentCommand`
215 `\stycmd_generate:NN \ProvideDocStyledCMD \ProvideDocumentCommand`

(End definition for \NewDocStyledCMD, \RenewDocStyledCMD, and \ProvideDocStyledCMD. These functions are documented on page 2.)

`\newstylecmdExp` Declare a new macro with the specified style name.
`\renewstylecmdExp` 216 `\stycmd_generate:NNN \newstylecmdExp \newcommand \stycmd_expcmd:N`
`\providestylecmdExp` 217 `\stycmd_generate_renew:NN \renewstylecmdExp \renewcommand`
218 `\stycmd_generate:NNN \providestylecmdExp \providecommand \stycmd_expcmd:N`

(End definition for \newstylecmdExp, \renewstylecmdExp, and \providestylecmdExp. These functions are documented on page 3.)

`\AddCMDToGroup` Creates a group of commands

```

219
220 \str_new:N \g__stycmd_grproxy_str
221 \seq_new:N \g__stycmd_tmp_seq
222 \seq_new:N \g__stycmd_tmpb_seq
223
224 \proxy_create_gset:NnnN \g__stycmd_grproxy_str { stycmd }{ groups }
225 \c_object_public_str
226
227 \proxy_push_member:Vnn \g__stycmd_grproxy_str { commands }{ seq }
228
229 \cs_generate_variant:Nn \seq_gconcat:NNN { ccN }
230
231 \cs_new_protected:Nn \__stycmd_gconcat:nN
232 {
233   \seq_gconcat:ccN { #1 }{ #1 } #2
234 }
235
236 \cs_new_protected:Nn \__stycmd_addgroup:nn
237 {
238   \object_if_exist:nF
239   {
240     \object_address:nn{ stycmd }{ group - #1 }
241   }
242   {
243     \object_create:VnnNN \g__stycmd_grproxy_str
244     { stycmd }
245     { group - #1 }
246     \c_object_global_str
247     \c_object_public_str
248   }

```

```

249
250 \seq_gset_from_clist:Nn \g__stycmd_tmp_seq { #2 }
251 \seq_gset_map_x:NNn \g__stycmd_tmpb_seq \g__stycmd_tmp_seq
252 {
253   \cs_to_str:N ##1
254 }
255
256 \__stycmd_gconcat:nN
257 {
258   \object_member_adr:nnn
259   {
260     \object_address:nn
261     { stycmd }
262     { group - #1 }
263   }
264   { commands }
265   { seq }
266   } \g__stycmd_tmpb_seq
267 }
268
269 \cs_generate_variant:Nn \__stycmd_addgroup:nn { fn }
270
271 \NewDocumentCommand{\AddCMDToGroup}{m m}
272 {
273   \__stycmd_addgroup:fn { \tl_trim_spaces:n{ #1 } } { #2 }
274 }
275

```

(End definition for `\AddCMDToGroup`. This function is documented on page 3.)

`\SetGroupStyle` Change the default style for each command in the group.

```

276 \NewDocumentCommand{\SetGroupStyle}{m m}
277 {
278   \seq_map_inline:cn
279   {
280     \object_member_adr:nnn
281     {
282       \object_address:nn
283       { stycmd }
284       { group - #1 }
285     }
286     { commands }
287     { seq }
288   }
289   {
290     \__stycmd_setdef_style:nn{ ##1 }{ #2 }
291   }
292 }

```

(End definition for `\SetGroupStyle`. This function is documented on page 3.)

Legacy commands

```

293
294 \msg_new:nnnn{ styledcmd }{ stydep }{ Old-fashioned-groups-for-styled-commands-are-deprecated
295 {

```

```

296     From~version~2.0~of~stylecmd~you~should~use~new~group~commands~instea~of~old~ones,~see~c
297 }
298
299 \str_new:N \g__stycmd_act_group_str
300 \str_new:N \g__stycmd_act_style_str
301
302 \NewDocumentCommand{\styBeginGroup}{ m }
303 {
304     \msg_warning:nn{ stylecmd }{ stydep }
305     \str_gset:Nn \g__stycmd_act_group_str{ #1 }
306 }
307
308 \NewDocumentCommand{\styEndGroup}{}
309 {
310     \msg_warning:nn{ stylecmd }{ stydep }
311     \str_gset:Nn \g__stycmd_act_group_str{}
312 }
313
314 \NewDocumentCommand{\styBeginStyle}{ m }
315 {
316     \msg_warning:nn{ stylecmd }{ stydep }
317     \str_gset:Nn \g__stycmd_act_style_str{ #1 }
318 }
319
320 \NewDocumentCommand{\styEndStyle}{}
321 {
322     \msg_warning:nn{ stylecmd }{ stydep }
323     \str_gset:Nn \g__stycmd_act_style_str{}
324 }
325
326 \cs_generate_variant:Nn \__stycmd_addgroup:nn { Vn }
327
328 \NewDocumentCommand{\newGstylecmd}{m o m}
329 {
330     \msg_warning:nn{ stylecmd }{ stydep }
331     \__stycmd_addgroup:Vn \g__stycmd_act_group_str { #1 }
332     \IfNoValueTF{ #2 }
333     {
334         \exp_args:NNV \newstylecmd #1 \g__stycmd_act_style_str { #3 }
335     }
336     {
337         \exp_args:NNV \newstylecmd #1 \g__stycmd_act_style_str [ #2 ] { #3 }
338     }
339 }
340
341 \NewDocumentCommand{\NewGDocStyledCMD}{m m m}
342 {
343     \msg_warning:nn{ stylecmd }{ stydep }
344     \__stycmd_addgroup:Vn \g__stycmd_act_group_str { #1 }
345     \exp_args:NNV \NewDocStyledCMD #1 \g__stycmd_act_style_str { #2 } { #3 }
346 }
347
348 \NewDocumentCommand{\setGroupStyle}{m m}
349 {

```

```
350     \msg_warning:nn{ styledcmd }{ stydep }
351     \SetGroupStyle{ #1 }{ #2 }
352   }
353 \end{package}
```